



PARADISE
ELECTRICAL INDUSTRIES
Speciality Cables

India's Largest Stockists/Channel Partner




Agilon



READY STOCK WITH PARADISE

Instrumentation Cables-Pair/Triad | Shielded Cables | Industrial Braided Cables | Fire Survival Cables | Fiber Optic | Solar AC/DC Cables | RS 485 Modbus Cables | LiYY/ LiYCY Cables | Audio-Video Cables | Rubber Cables | Flat Festoon Cables | Thermocouple & Compensating Cables | High Temperature Cables | Spiral Cables | MICC Cables | Water Cooled Cables | UL / CSA Approved Cables | VFD cables | Profibus Cables | Field Bus cables | Tactical Fibre/Lan Cables | Special Cables / Custom as per Client specification.




READY STOCK

SHIELDED (FOIL) CABLES

Range : 2 to 61 Cores, 1P to 24 Pairs, Size 0.5 to 2.5 sq.mm & 2,3 & 4 Core in sizes 4 to 6 sq.mm

Specification : Flexible Bare / Tinned Copper Conductor, PVC Insulated, Cross Laid up / Paired overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC/FRLS Outer Sheath BMS Cables 300/500 Volts.

Armoured Versions Also available.




READY STOCK

SHIELDED CABLES (100% COVERAGE)

Range : 2 to 64 Cores, 1P to 24 Pairs, Size 0.5 to 2.5 sq.mm & 3 & 4 Core in sizes 4 to 16sq.mm

Specification : Annealed Bare / Tinned Copper Flexible Conductor, PVC Insulated, Aluminium Mylar tape with Tinned Cu Braided, PVC/FRLS Sheathed Flexible Unarmoured Cables 1100 Volts.




READY STOCK

SHIELDED (BRAIDED) CABLES

Range : 2 to 100 Cores, Size 0.5 to 2.5 sq.mm & 3 & 4 Core in sizes 4 to 240 sq.mm

Specification : Annealed Bare / Tinned Copper Flexible Conductor, PVC Insulated, PVC Inner sheathed, Tinned Cu Braided, PVC/FRLS Sheathed Flexible. Unarmoured Cables 1100 Volts.



READY STOCK

FIRE ALARM CABLES

Range : 2 to 8 Cores, Size 0.5 to 2.5 sq.mm

Specification : Solid / Flexible Bare / Tinned Copper Conductor, PVC Insulated, Cross Laid up overall Aluminium Mylar Tape Shielded along with ATC Drain Wire, FRLS Outer Sheath Red Unarmd Fire Alarm Cables 300/500 Volts.

Armoured Versions Also available.



READY STOCK

FIRE SURVIVAL MINERAL INSULATED CABLES

Range : 1, 2, 3 & 4 Cores, Size 0.5 to 2.5 sq.mm

FIRE SURVIVAL CABLES	
Construction	Solid bare copper
Conductor	With Mica tape / Without Mica tape
1. Flame Barrier	Cross Linked HFFR / Silicone Rubber Insulation
Insulation	Fiber glass tape / Without FG tape.
2. Flame Barrier	Aluminium laminated polyester tape
Shield	D.08 mm Solid tinned copper
Drain Wire	HFFR
Sheath	HFFR

MINERAL INSULATED CABLES
MICC Cables is a electrical cable made from copper conductors inside a copper sheath insulated by inorganic magnesium oxide powder and HFFR Sheathed.

LPCB
Loss Prevention Certification Board
Certificate No: 7115-(d-1)
Certificate No: 7115-(d-6)



READY STOCK

LAN & FIBRE OPTIC CABLES

Range : Cat 5e & 6

Specification : CU/CCS/CCA Conductor, Twisted Pair, Insulated with High Quality Polyethylene and Shielded /Unshielded Light Grey FR PVC Jacket.

(Cat 6 Armoured / Shielded Versions also available.)

FIBRE OPTIC CABLES
"Finolex" Single & Multimode Versions, Fiber Optic Cables Up to 24 fibers.




READY STOCK

SPEAKER CABLES

Range : Twin Parallel/Twin Twisted 23/36, 23/38, 40/36 and 40/38

Specification : Available on request Speaker Cables with high quality oxygen free copper conductor ensuring excellent sound quality for your expensive Sound system.



READY STOCK

COPPER ARMED /FLEX. CABLES (LARGE SIZES)

Range : 3, 3.5 & 4 Cores, Size 25 to 300 sq.mm

Specification : Power Copper Armd Cables, Stranded , XLPE / PVC Insulated, cores laid up, PVC/FR/ST2/FRLS/extruded inner sheath, Strip Armd, extruded PVC/FR/ST2/FRLS sheathed cables as per IS 7098.

FLEXIBLE CABLES
Specification : Copper conductors with PVC Insulation and PVC/FRLS sheathing properties.



RS 485 SCREENED CABLES

Range : 1 P to 4 Pair,
Size 24/22/20 AWG

Specification : Tinned Copper Conductor
Polyethylene insulation, Twisted
into pairs, overall aluminium/polyester foil
screened, tinned copper drain wire (24AWG),
overall tinned copper braid (90%). PVC sheath.

Armoured Versions Also available.



BUS CABLES

Range : 18 to 24 AWG,
Upto 4 Pair

Specification : Available on request.
We have wide range of Industrial Bus Cables
in stock Like Profibus, Can Bus,
Modbus Cables, Fieldbus, Industrial
Twinax Cables, VFD cables, Device net
cables & Other Data Cables.



INSTRUMENTATION CABLES (OVERALL SHIELDED)

Range : 1 Pair/Traid to 61 Pair/Traid/Core,
sizes 0.5 sq.mm to 2.5 sq.mm

Specification : Stranded/Solid Copper Conductor,
PE/PVC/HR-PVC/XLPE, Core/Pair/Triad/Quad laid up
together overall shielded with Mylar/Drain Wire/
Al Mylar, PE / PVC/FRLS/PVC ST 2/LSOH Inner sheathed,
Unarmoured/GI Steel round wire/Strip/GI Steel Wire braided
(Armoured), PVC/FR/FRLS/PVC ST2/LSOH Outer Sheathed.



CO-AXIAL CABLES

Range : RG 59 F, RG 6 F, RG 6 CCS
RG 11 F, RG 11 F CCS, RG 213, RG 214,
RG 8, RG 224, RG 58 and many more.

Specification : CU/CCS/CCA Conductor,
Nitrogen Gas Injected polyethylene
foam insulation / Solid PE,
composite Al foil laminated and Al-alloy/
Cu braided , PVC/FRLS Sheathed.

Armoured Versions Also available.



INSTRUMENTATION CABLES (INDIVIDUAL + OVERALL SHIELDED)

Range : 1 Pair/Traid to 61 Pair/Traid/Core,
sizes 0.5 sq.mm to 2.5 sq.mm

Specification : Individual and Overall Shielded Cables
Stranded/Solid Copper Conductor, PE/PVC /HR-PVC/
XLPE Insulated each Pair/Triad laid up shielded with Mylar/
Drain Wire/Al Mylar, all Pairs/Triads then laid up overall shielded
with Mylar/Drain Wire/Al Mylar, PE/PVC/FRLS /PVC ST 2/LSOH
sheathed Unarmoured/GI Steel round Wire/Strip (Armoured) /GI Steel
Wire braided, PVC/FR/FRLS/PVC ST2/LSOH Outer Sheathed.



AUDIO / VIDEO CABLES

Range :
Unbalanced/Balanced Microphone Cable,
Single Pair Balanced Cables,
Loud Speaker Cables,
Highly Flexible Speaker Cables

Design : In these cables, OFC (Oxygen
Free Copper) Conductor is being preferred to
minimize the loss in the signals. With the
Protective Shielding, signals are being protected
from the effects of RFI and EMI, the noise and
signal distortion. For easy-installation and use, flexible
and highquality materials are preferred for insulation.



SOLAR CABLES

Range : 1.5 to 240 sq.mm x1C
1.0 to 16 sq.mm x 2, 3 & 4C

Specification : Flexible Tinned Copper
Conductor, Cross Linked, Zero Halogen Low
Smoke Insulation and Cross Linked Low Smoke
Sheathing, Heat Resistant upto 120°C and
UV Resistant Solar Cables as Per TUV Specs. (Type 1)



SNAKE CABLES

Range : 4 to 48 Pairs
Size 22 & 24 AWG

Specification : Multicore individual and
overall foil shielded / Cu Wire Spiral shielded /
Overall ATC braided cables are designed
and ideal for fixed installation of
transmission of analog audio signals.

READY STOCK



- ✓ Single Core Cables
- ✓ Control Flexible Cables
- ✓ Shielded Cables
- ✓ Industrial Braided Cables
- ✓ Instrumentation Cables-Pair/Triad
- ✓ LiYY/LiYCY Cables
- ✓ Fire Survival Cables
- ✓ Solar AC/DC Cables
- ✓ RS-485 Cables
- ✓ Bus Cables
- ✓ Profibus Cables
- ✓ Field Bus Cables
- ✓ KNX Cables
- ✓ CAN Bus Cables
- ✓ Fiber Optic Cables
- ✓ Audio-Video Cables
- ✓ Rubber Cables
- ✓ Flat Festoon Cables
- ✓ Coaxial Cables
- ✓ Lan Cables
- ✓ Telephone Cables
- ✓ Jelly Filled Cables
- ✓ Riser Cables
- ✓ LT Copper Armoured Cables
- ✓ LT Aluminium Armoured Cables
- ✓ HT Aluminium Armoured Cables
- ✓ Teflon Cables
- ✓ Silicone Cables
- ✓ Fibre Glass Cables
- ✓ Thermocouple & Compensating Cables
- ✓ MICC Cables
- ✓ Spiral Cables
- ✓ Water Cooled Cables
- ✓ UL/CSA Approved Cables
- ✓ VFD Cables
- ✓ Medical Cables
- ✓ Military, Aerospace & Defence Cables
- ✓ Tactical Fibre Optic Cables
- ✓ Tactical Lan Cables
- ✓ Special Cables as per client's specs



Regd. office :

Paradise Electrical Industries

3815, Babu Wali Gali, Mori Gate, Delhi-110006

Ph.: +91-11-23983111, 23981664, 23981222, 45072885

E-mail : enquiry@paradisespecialitycables.com
quote@paradisespecialitycables.com

Website : <https://www.paradisespecialitycables.com>